

WorkForce Pro WF-C529RDW

DATASHEET / BROCHURE



Fast print speeds with a smaller footprint, our latest A4 RIPS printer delivers low TCO and a low environmental impact.

High ink yields of up to 50,000 pages in black and 20,000 in colour make this a powerhouse for offices. Increase your business productivity with less intervention, a fast first page out time, and secure printing rules and workflow processes, all while reducing your printing costs and environmental impact.

Low running costs

High ink yields lower the need to order and replace supplies frequently, and help to deliver predictable print costs and a competitive Total Cost of Ownership (TCO). Also, inkjet technology with fewer replacement parts, lowers the hidden costs of servicing and intervention.

High productivity

A fast First Page Out Time (FPOT) of 4.8 secs in black and 5.3 secs in colour from ready mode, and print speeds of up to 24ppm in colour and mono (ISO speed) help to keep productivity high. An improved durability of 240k pages helps print more for longer. A maximum paper capacity of 1,330 sheets means less time spent refilling.

Low environmental impact

In addition to speeding up printing, the lack of heat needed by our inkjet technology also helps to cut the environmental impact of print by providing a low power solution with fewer supplies. The high ink yield means less waste from supplies, and you can rest assured from a lack of toner dust and ozone gas emissions.

Built for business

The WF-C529RDW is one of the few A4 business single-function printers to offer secure, follow-me printing with Epson Print Admin.

KEY FEATURES

- **Low running costs**
Benefit from a low Total Cost of Ownership
- **Fast FPOT**
4.8secs in black and 5.3 secs in colour from ready mode
- **Small footprint**
Easier to position in the office or space-critical workplaces
- **Lower your environmental impact**
Low energy consumption reduces CO2 footprint, no ozone gas emissions
- **Secure, follow-me printing**
With Epson Print Admin

EPSON®

PRODUCT SPECIFICATIONS

TECHNOLOGY

Printing Method	PrecisionCore™ Print Head
Nozzle Configuration	800 Nozzles Black, 800 Nozzles per Color
Minimum Droplet Size	3.8 pl, With Variable-Sized Droplet Technology
Ink Technology	Replaceable Ink Pack System (RIPS)
Category	Office Workgroup
All-in-One Functions	Print

PRINT

First Page Out	Monochrome 4.8 Seconds, Colour 5.3 Seconds
Printing Speed ISO/IEC 24734	24 pages/min Monochrome, 24 pages/min Colour
Duplex Printing Speed ISO/IEC 24734	15 A4 Pages/min Monochrome, 15 A4 Pages/min Colour
Maximum Printing Speed	34 pages/min Monochrome (plain paper 75 g/m ²), 34 pages/min Colour (plain paper 75 g/m ²)
Printing Resolution	4,800 x 1,200 DPI
Printing Volume	50,000 pages per month The maximum number of printed pages per month based on the performance capabilities of the printer, including ISO rated print speeds and paper handling capabilities.
Recommended Duty Cycle	400 - 4,500 pages per month
Colours	Black, Cyan, Yellow, Magenta

For detailed information on printing speeds please visit <http://www.epson.eu/testing>.

CONNECTIVITY

Network Printing Protocols	LPR, FTP, IPP, LDP, Port 9100, WSD-Print
Network Management Protocols	HTTP, DHCP, BOOTP, APIPA, DDNS, mDNS, SNTP, ENPC, SLP, WSD, LLTD, SMTP, LLMNR, POP3, IEEE 802.1X, ARP, GARP, EAP, ICMP, IGMP, DNS-SD, HTTPS, XMPP, LDAP, LDAPS, SNMP 3.0, SNMP Trap
Interfaces	Hi-Speed USB - compatible with USB 2.0 specification, Ethernet Interface (1000 Base-T/ 100-Base TX/ 10-Base-T), Wireless LAN IEEE 802.11b/g/n, Wi-Fi Direct, USB 2.0-A
WLAN Security	WEP 64 Bit, WEP 128 Bit, WPA PSK (TKIP), WPA2 PSK (AES), WPA2 Enterprise (AES)
Network Protocol	TCP/IPv4, TCP/IPv6, HTTP, HTTPS, IPSEC

WorkForce Pro WF-C529RDW

WHAT'S IN THE BOX

- Driver and utilities
- Power cable
- Quick Setup Guide
- User manual (CD)
- Warranty Documents
- Initialization Ink Supply Units

PRODUCT SPECIFICATIONS

WorkForce Pro WF-C529RDW

PAPER / MEDIA HANDLING

Paper Formats	A4 (21.0x29.7 cm), A5 (14.8x21.0 cm), A6 (10.5x14.8 cm), B5, B6, C4 (Envelope), C6 (Envelope), DL (Envelope), No. 10 (Envelope), Letter, Legal, 9 x 13 cm, 10 x 15 cm, 13 x 18 cm, 16:9, HLT, EXE, User defined
Compatible Paper Weight	64 - 300g/m ²
Duplex	Yes
Standard Paper input	250 Sheets Standard, 80 Sheets MP tray
Output Tray Capacity	150 Sheets
Paper Tray Capacity	330 Sheets Standard, 1,330 Sheets Maximum
Standard paper tray(s)	80-Sheet Multi-Purpose Tray, 250-sheet paper tray, 500-Sheet paper tray
Optional paper tray(s)	500-Sheet paper tray
Rear paper path (special media)	Yes
Number of paper trays	2

PAPER FEED RASF

Paper Input Name	RASF
Paper Formats	A4, A5, A6, B5, B6, C4 (Envelope), C6 (Envelope), DL (Envelope), No. 10 (Envelope), Letter, 10 x 15 cm, 13 x 18 cm, 16:9, Legal, Executive
Custom sizes	Min64x 127 mm to Max 215.9x 6,000 mm
Compatible paper weight	64 g/m ² - 300 g/m ²
Paper Capacity 1	80 Sheets of Plain Paper, 80gsm
Media type	Plain Paper, Recycled Paper, Colour Paper, Letterhead, Glossy Photo Paper

PAPER FEED C1

Paper Input Name	C1
Paper Formats	A4, A5, A6, B5, B6, C4 (Envelope), C6 (Envelope), DL (Envelope), No. 10 (Envelope), Letter, HLT, Executive
Custom sizes	Min89x 127 mm to Max 215.9x 355.6 mm
Compatible paper weight	64 g/m ² - 300 g/m ²
Paper Capacity 1	250 Sheets of Plain Paper, 80gsm
Media type	Plain Paper, Recycled Paper, Colour Paper, Letterhead, Glossy Photo Paper

PAPER FEED C2

Paper Input Name	C2
Paper Formats	A4, A5, A6, B5, B6, Letter, HLT, LGL, Executive
Custom sizes	Min100x 148 mm to Max 215.9x 355.6 mm
Compatible paper weight	64 g/m ² - 160 g/m ²
Paper Capacity 1	500 Sheets of Plain Paper, 80gsm
Media type	Plain Paper, Recycled Paper, Colour Paper, Letterhead

PAPER FEED DUPLEX

Paper Input Name	Duplex
Paper Formats	A4, A5, A6, B5, B6, Letter, HLT, Legal, Executive
Custom sizes	Min148x 210 mm to Max 216x 297 mm
Compatible paper weight	64 g/m ² - 160 g/m ²
Media type	Plain Paper, Recycled Paper, Colour Paper, Letterhead

PAPER FEED C3

Paper Input Name	C3
Paper Formats	A4, A5, A6, B5, B6, Letter, HLT, Legal, Executive
Custom sizes	Min100x 148 mm to Max 215.9x 355.6 mm
Compatible paper weight	64 g/m ² - 160 g/m ²
Paper Capacity 1	500 Sheets of Plain Paper, 80gsm
Media type	Plain Paper, Recycled Paper, Colour Paper, Letterhead

PRODUCT SPECIFICATIONS

WorkForce Pro WF-C529RDW

GENERAL	
Energy Use	1.2 Watt (sleep mode), 24 Watt (Printing), 8 Watt (Ready), 0.2 Watt (Power off), TEC 0.18 kWh/week
Supply Voltage	AC 220 V - 240 V, 50 Hz - 60 Hz
Product dimensions	425 x 535 x 413 mm (Width x Depth x Height)
Product weight	19.3 kg
Compatible Operating Systems	Mac OS 10.10.x, Mac OS 10.7.x, Mac OS 10.8.x, Mac OS 10.9.x, Mac OS X 10.11.x, Mac OS X 10.12.x, Mac OS X 10.6.8 or later, Windows 10, Windows 7, Windows 7 x64, Windows 8, Windows 8 (32/64 bit), Windows 8.1, Windows 8.1 x64 Edition, Windows Server 2003 R2 x64, Windows Server 2008 (32/64bit), Windows Server 2008 R2, Windows Server 2012 (64bit), Windows Server 2012 R2, Windows Server 2016, Windows Vista, Windows Vista (32/64 bit), Windows Vista x64, Windows XP SP2 or higher, Windows XP SP3, Windows XP x64, Windows Server 2003 R2, XP Professional x64 Edition, XP Professional x64 Edition SP2
Sound Power	Operation:6.9 B (A)
Noise	Operation:54 dB (A)
Mobile and Cloud printing services	Epson Connect (iPrint, Email Print, Remote Print Driver), Apple AirPrint, Google Cloud Print
Power supply	220V, 240V
ADDITIONAL FEATURES	
Features	Direct Print, Direct print from USB
Panel	Type: Color, Diagonal:6.1 cm
Media Handling	Automatic duplex (A4, plain paper), Portrait & Landscape printing, Thick Media Support
Security Functions	Limit access function with Epson Web Config, Secure confidential printing with PIN code release, LDAP Address Book, IPsec, IEEE802.1x, SSL (Server authentication), Panel Admin Mode
PRODUCT SAFETY	
Product Safety Warnings	Contains 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction. Contains 2,4,7,9-tetramethyldec-5-yne-4,7-diol. May produce an allergic reaction. Contains 2-methylisothiazol-3(2H)-one. May produce an allergic reaction. Always follow the information on the product label.
OTHER FEATURES	
Emulations	PCL5c, PCL6, ESC/P-R, PostScript 3, PDF 1.7

SUPPLIES

● WorkForce Pro WF-C529R / C579R Magenta XL Ink Supply Unit	C13T01C300	5,000 lehekülge
● WorkForce Pro WF-C529R / C579R Yellow XL Ink Supply Unit	C13T01C400	5,000 lehekülge
● WorkForce Pro WF-C529R / C579R Cyan XL Ink Supply Unit	C13T01C200	5,000 lehekülge
● WorkForce Pro WF-C529R / C579R Black XL Ink Supply Unit	C13T01C100	10,000 lehekülge
● WorkForce Pro WF-C529R / C579R Black XXL Ink Supply Unit	C13T01D100	50,000 lehekülge
● WorkForce Pro WF-C529R / C579R Cyan XXL Ink Supply Unit	C13T01D200	20,000 lehekülge
● WorkForce Pro WF-C529R / C579R Magenta XXL Ink Supply Unit	C13T01D300	20,000 lehekülge
● WorkForce Pro WF-C529R / C579R Yellow XXL Ink Supply Unit	C13T01D400	20,000 lehekülge
● Maintenance box	C13T671600	

LOGISTICS INFORMATION

SKU	C11CG79401
EAN code	8715946653471
Country of Origin	Indonesia
Layer	2 Units

WorkForce Pro WF-C529RDW

INK YIELD DATA



●	10,000 pages*	50,000 pages*
● ● ●	5,000 pages*	20,000 pages*

* Approx. page yield based on ISO/IEC 24711/24712 or ISO/IEC 29102/29103. Actual yield will vary depending on images printed and usage conditions. For more information visit <http://www.epson.eu/pageyield>

* Warranty offers are not available for all countries. Please contact your local Epson representative.

For further information please contact your local Epson office or visit www.epson-europe.com
Austria 01 253 49 78 333 Belgium +32 (0)2 792 04 47 Czech 800/142 052 Denmark 44 50 85 85 Finland 0201 552 091 France 09 74 75 04 04
(Cost of local call, operator charges may apply) Germany +49 (0) 2159/92 79 500 Greece +30 211 198 62 12 Hungary 06800 147 83 Ireland 01 436 7742
Italy 02-660321 10 (0,12 /min) Luxembourg +352 27860692 Middle East +9714 8872172 Netherlands +31 (0)20 708 5099 Norway +47 67 11 37 00
Poland 0-0-800 4911299 (0,16 zł/min) Portugal 707 222 111 Russia (095) 777-03-55 Slovakia 0850 111 429 South Africa (+2711) 465-9621
Spain 93 582 15 00 Sweden 0771-400135 (Mobilsamtal – 0,99 kr/min, Lokala samtal – 0,30 kr/min, Utlandssamtal – 0,89 kr/min)
Switzerland 022 592 7923
Turkey (0212) 3360303 United Kingdom 0871 222 6702

Trademarks and registered trademarks are the property of Seiko Epson Corporation or their respective owners.
Product information is subject to change without prior notice.

EPSON®